


Miscellaneous Brass Valves

"Y" Strainer

Suitable for hydraulic and pneumatic applications.
Max operating temperature 90°C



Order Code	Size	Maximum Pressure	RRP Price	List Price
23075-04	1/4 BSP	2000kPa	10.22	6.81
23075-06	3/8 BSP	2000kPa	10.25	6.83
23075-08	1/2 BSP	2000kPa	14.64	9.76
23075-12	3/4 BSP	2000kPa	15.54	10.36
23075-16	1 BSP	2000kPa	24.57	16.38
23075-20	1 1/4 BSP	2000kPa	36.57	24.38
23075-24	1 1/2 BSP	2000kPa	48.42	32.28
23075-32	2 BSP	2000kPa	80.51	53.67
23075-48	3 BSP	1580kPa	267.71	178.47
23075-64	4 BSP	1580kPa	554.48	369.65

Brass Gate Valve - Untested

Suitable for non drinking water.
Max operating temperature 60°C



Order Code	Size	Maximum Pressure	RRP Price	List Price
23003-04	1/4 BSP	820kPa	12.84	8.56
23003-06	3/8 BSP	820kPa	12.84	8.56
23003-08	1/2 BSP	820kPa	11.07	7.38
23003-12	3/4 BSP	820kPa	13.01	8.67
23003-16	1 BSP	820kPa	18.29	12.19
23003-20	1 1/4 BSP	820kPa	28.58	19.05
23003-24	1 1/2 BSP	820kPa	38.00	25.33
23003-32	2 BSP	820kPa	54.83	36.55
23003-40	2 1/2 BSP	820kPa	112.86	75.24
23003-48	3 BSP	820kPa	140.04	93.36
23003-64	4 BSP	820kPa	253.11	168.74

Swing Check Valve

Suitable for non drinking water.
Max operating temperature 60°C



Order Code	Size	Maximum Pressure	RRP Price	List Price
23004-08	1/2 BSP	1170kPa	15.05	10.03
23004-12	3/4 BSP	1170kPa	20.91	13.94
23004-16	1 BSP	1170kPa	29.25	19.50
23004-20	1 1/4 BSP	960kPa	42.66	28.44
23004-24	1 1/2 BSP	960kPa	54.96	36.64
23004-32	2 BSP	960kPa	78.09	52.06
23004-40	2 1/2 BSP	750kPa	122.52	81.68

York Check & Foot Valves

Suitable for hydraulic and pneumatic applications.
Max operating temperature 80°C



Order Code	Size	Maximum Pressure	RRP Price	List Price
23151-06	3/8 BSP	1170kPa	10.38	6.92
23151-08	1/2 BSP	1170kPa	10.34	6.89
23151-12	3/4 BSP	1170kPa	14.58	9.72
23151-16	1 BSP	1170kPa	18.96	12.64
23151-20	1 1/4 BSP	960kPa	27.47	18.31
23151-24	1 1/2 BSP	960kPa	41.51	27.67
23151-32	2 BSP	960kPa	57.84	38.56
23151-40	2 1/2 BSP	750kPa	108.84	72.56
23151-48	3 BSP	750kPa	154.83	103.22
23151-64	4 BSP	750kPa	267.96	178.64

Miscellaneous Brass Valves


Valstop Check Valves - C/W Viton O-Ring

Operating temperature range -20°C to 135°C. Quoted maximum pressure at 20°C. Viton seals are recommended when using carbon fuels.



Order Code	Size	Maximum Pressure	RRP Price	List Price
23151-04V	1/4 BSP	4800kPa	34.89	23.26
23151-06V	3/8 BSP	4800kPa	34.89	23.26
23151-08V	1/2 BSP	4000kPa	37.11	24.74
23151-12V	3/4 BSP	3500kPa	45.15	30.10
23151-16V	1 BSP	3000kPa	60.23	40.15
23151-24V	1 1/2 BSP	2500kPa	137.75	91.83
23151-32V	2 BSP	2000kPa	225.00	150.00

York Check & Foot Valves - Strainer Only



Order Code	Size	RRP Price	List Price
23154-06	3/8 BSP	3.38	2.25
23154-08	1/2 BSP	3.57	2.38
23154-12	3/4 BSP	3.95	2.63
23154-16	1 BSP	4.50	3.00
23154-20	1 1/4 BSP	5.88	3.92
23154-24	1 1/2 BSP	7.76	5.17
23154-32	2 BSP	9.75	6.50
23154-40	2 1/2 BSP	19.50	13.00
23154-48	3 BSP	24.06	16.04
23154-64	4 BSP	32.51	21.67