

Reinforced PVC Hose

ESY Safety Yellow - General Purpose Hose (Reinforced PVC)

Pressure ratings calculated at 20 degrees Celsius.
 Operating temperature zero to 60 degrees Celsius
 Tough ribbed cover for added abrasion resistance
 Suitable for air or water delivery (industrial applications)



Order Code	NOM ID	NOM OD	Working Pressure	Burst Pressure	Coil Length	RRP Per Mtr	List Per Mtr
13007-04	1/4 (6mm)	12.0mm	1600kPa	6400kPa	20, 100	2.65	1.76
13007-05	5/16 (8mm)	14.0mm	1600kPa	6400kPa	20, 100	2.94	1.96
13007-06	3/8 (10mm)	17.0mm	2000kPa	8000kPa	20, 100	3.33	2.22
13007-08	1/2 (12mm)	19.0mm	1600kPa	6400kPa	20, 100	4.64	3.09
13007-12	3/4 (19mm)	28.0mm	1600kPa	6400kPa	20, 100	10.58	7.05
13007-16	1 (25mm)	34.0mm	1600kPa	6400kPa	20	12.38	8.25
13007-20	1 1/4 (32mm)	44.0mm	1600kPa	6400kPa	20	18.91	12.61
13007-24	1 1/2 (40mm)	51.0mm	1600kPa	6400kPa	20	31.52	21.01
13007-32	2 (50mm)	69.0mm	1600kPa	6400kPa	20	44.57	29.71

Petrol Resistant / Food Contact Hose (Reinforced PVC)

Ideal for selected solvents and fuels
 Red tracer for identification as a fuel line
 Pressure ratings calculated at 20 degrees Celsius
 Operating temperature zero to 60 degrees Celsius



Order Code	NOM ID	NOM OD	Working Pressure	Burst Pressure	Coil Length	RRP Per Mtr	List Per Mtr
13350-04	1/4 (6mm)	11.0mm	1600kPa	6400kPa	20, 100	2.79	1.86
13350-05	5/16 (8mm)	13.0mm	1600kPa	6400kPa	20, 100	3.09	2.06
13350-06	3/8 (10mm)	17.0mm	1600kPa	6400kPa	20, 100	3.78	2.52
13350-08	1/2 (12mm)	18.1mm	1600kPa	6400kPa	20, 100, 200	4.95	3.30
13350-10	5/8 (16mm)	22.0mm	1600kPa	6400kPa	20	6.08	4.05
13350-12	3/4 (19mm)	27.6mm	1600kPa	6400kPa	20	9.76	6.51
13350-16	1 (25mm)	33.5mm	1600kPa	6400kPa	20	13.28	8.85
13350-20	1 1/4 (32mm)	41.8mm	1000kPa	4000kPa	20	19.81	13.21
13350-24	1 1/2 (40mm)	52.4mm	900kPa	3600kPa	20	34.67	23.11
13350-32	2 (50mm)	62.0mm	900kPa	3600kPa	20	49.52	33.02