

## Reinforced PVC Hose

### ESY Safety Yellow - General Purpose Hose (Reinforced PVC)

Pressure ratings calculated at 20 degrees Celsius.  
 Operating temperature zero to 60 degrees Celsius  
 Tough ribbed cover for added abrasion resistance  
 Suitable for air or water delivery (industrial applications)



| Order Code | NOM ID       | NOM OD | Working Pressure | Burst Pressure | Coil Length | RRP Per Mtr | List Per Mtr |
|------------|--------------|--------|------------------|----------------|-------------|-------------|--------------|
| 13007-04   | 1/4 (6mm)    | 12.0mm | 1600kPa          | 6400kPa        | 20, 100     | 2.65        | 1.76         |
| 13007-05   | 5/16 (8mm)   | 14.0mm | 1600kPa          | 6400kPa        | 20, 100     | 2.94        | 1.96         |
| 13007-06   | 3/8 (10mm)   | 17.0mm | 2000kPa          | 8000kPa        | 20, 100     | 3.33        | 2.22         |
| 13007-08   | 1/2 (12mm)   | 19.0mm | 1600kPa          | 6400kPa        | 20, 100     | 4.64        | 3.09         |
| 13007-12   | 3/4 (19mm)   | 28.0mm | 1600kPa          | 6400kPa        | 20, 100     | 10.58       | 7.05         |
| 13007-16   | 1 (25mm)     | 34.0mm | 1600kPa          | 6400kPa        | 20          | 12.38       | 8.25         |
| 13007-20   | 1 1/4 (32mm) | 44.0mm | 1600kPa          | 6400kPa        | 20          | 18.91       | 12.61        |
| 13007-24   | 1 1/2 (40mm) | 51.0mm | 1600kPa          | 6400kPa        | 20          | 31.52       | 21.01        |
| 13007-32   | 2 (50mm)     | 69.0mm | 1600kPa          | 6400kPa        | 20          | 44.57       | 29.71        |

### Petrol Resistant / Food Contact Hose (Reinforced PVC)

Ideal for selected solvents and fuels  
 Red tracer for identification as a fuel line  
 Pressure ratings calculated at 20 degrees Celsius  
 Operating temperature zero to 60 degrees Celsius



| Order Code | NOM ID       | NOM OD | Working Pressure | Burst Pressure | Coil Length  | RRP Per Mtr | List Per Mtr |
|------------|--------------|--------|------------------|----------------|--------------|-------------|--------------|
| 13350-04   | 1/4 (6mm)    | 11.0mm | 1600kPa          | 6400kPa        | 20, 100      | 2.79        | 1.86         |
| 13350-05   | 5/16 (8mm)   | 13.0mm | 1600kPa          | 6400kPa        | 20, 100      | 3.09        | 2.06         |
| 13350-06   | 3/8 (10mm)   | 17.0mm | 1600kPa          | 6400kPa        | 20, 100      | 3.78        | 2.52         |
| 13350-08   | 1/2 (12mm)   | 18.1mm | 1600kPa          | 6400kPa        | 20, 100, 200 | 4.95        | 3.30         |
| 13350-10   | 5/8 (16mm)   | 22.0mm | 1600kPa          | 6400kPa        | 20           | 6.08        | 4.05         |
| 13350-12   | 3/4 (19mm)   | 27.6mm | 1600kPa          | 6400kPa        | 20           | 9.76        | 6.51         |
| 13350-16   | 1 (25mm)     | 33.5mm | 1600kPa          | 6400kPa        | 20           | 13.28       | 8.85         |
| 13350-20   | 1 1/4 (32mm) | 41.8mm | 1000kPa          | 4000kPa        | 20           | 19.81       | 13.21        |
| 13350-24   | 1 1/2 (40mm) | 52.4mm | 900kPa           | 3600kPa        | 20           | 34.67       | 23.11        |
| 13350-32   | 2 (50mm)     | 62.0mm | 900kPa           | 3600kPa        | 20           | 49.52       | 33.02        |