

Uniflex Airline Hose & Assemblies

Uniflex Airline Hose (Reinforced PVC)

Meets AS2554 Class B

Pressure ratings calculated at 20 degrees Celsius.

Operating temperature minus 20 to 60 degrees Celsius

Remains flexible at very low temperatures

Suitable for air or water delivery (industrial applications)



Order Code	NOM ID	NOM OD	Working Pressure	Burst Pressure	Coil Length	RRP Per Mtr	List Per Mtr
13904-04	1/4 (6mm)	12.4mm	1700kPa	6800kPa	20, 100, 200, 300	2.89	1.93
13904-05	5/16 (8mm)	14.0mm	1700kPa	6800kPa	20, 100, 200, 300	2.98	1.99
13904-06	3/8 (10mm)	16.4mm	1700kPa	6800kPa	20, 100, 200, 300	3.17	2.11
13904-08	1/2 (12mm)	18.9mm	1700kPa	6800kPa	20, 100, 200, 300	4.38	2.92

Uniflex Airline Hose Assemblies

Pre-fitted with coupling & adaptor



Order Code	NOM ID	HOSE LENGTH	Fitting Style	Coupling	Adaptor	RRP Per Coil	List Per Coil
13904-20-06N	3/8 (10mm)	20 mtr	Nitto	30SH	30PH	106.13	70.75
13904-20-06R	3/8 (10mm)	20 mtr	Ryco	241S	206AS	85.66	57.11
13904-30-06C	3/8 (10mm)	30 mtr	Cejn	541	506A	126.80	84.53
13904-30-06N	3/8 (10mm)	30 mtr	Nitto	30SH	30PH	131.14	87.42
13904-30-06R	3/8 (10mm)	30 mtr	Ryco	241S	206AS	104.45	69.63

Uniflex Airline Hose (Reinforced PVC) -Yellow Stripe



Order Code	NOM ID	NOM OD	Working Pressure	Burst Pressure	Coil Length	RRP Per Mtr	List Per Mtr
13904-06S	3/8 (10mm)	16.4mm	1700kPa	6800kPa	20	3.26	2.17
13904-08S	1/2 (12mm)	18.9mm	1700kPa	6800kPa	20	4.49	2.99